

Instalatii de incalzire/racire radianta

Lista elementelor livrate

- Distribuitor inox cu debitmetre
- Colector inox cu ventile termostactice
- Set suporti metalici montaj distribuitor/colector
- Piese de capat cu ventil aerisire si robinet golire

Date tehnice

Material corp distribuitor/colector: Inox AISI304

Material ventile si accesorii: Alama CW617N

Diametru corp distribuitor/colector: 1

Diametru racordare distribuitor/colector (capat): 1

Diametru conexiune circuite: 3/4

Temperatura maxima utilizare: 70°C

Presiune maxima utilizare: 6 bar pentru agent termic apa calda conform VDI 2035

Dimensiune ventil retur: M30x1.5



Reglaj debitmetru: 0-2.5l/min












Tip fluid acceptat: Apa si Apa + Glycol (max30%)

Distanta interax circuite: 50 mm

Distanta interax racorduri capete: 200 mm

Articole

SKU	Poza	Numar circuite incalzire	Lungime distribuitor	Unitate masura
1DDB3702		2	215mm	buc
1DDB3703		3	265mm	buc

1DDB3704		4	315mm	buc
1DDB3705		5	365mm	buc
1DDB3706		6	415mm	buc
1DDB3707		7	465mm	buc
1DDB3708		8	515mm	buc
1DDB3709		9	565mm	buc
1DDB3710		10	615mm	buc
1DDB3711		11	665mm	buc
1DDB3712		12	715mm	buc
1DDB3713		13	765mm	buc
1DDB3714		14	815mm	buc

1DDB3715



15

865mm

buc