



Tabel cedare caldura RADIATOARE HEKO ELCHE - in Watt conform EN 442									
	90/70/20°C			75/65/20°C			55/45/20°C		
LATIME	INALTIME			INALTIME			INALTIME		
[mm]	800	1200	1800	800	1200	1800	800	1200	1800
500	356	573	818	285	459	655	153	246	351
600	406	658	936	325	527	750	174	282	402

Tabel cedare caldura RADIATOARE HEKO JET - in Watt conform EN 442									
	90/70/20°C			75/65/20°C			55/45/20°C		
LATIME	INALTIME			INALTIME			INALTIME		
[mm]	800	1200	1800	800	1200	1800	800	1200	1800
500	356	573	818	285	459	655	153	246	351
600	406	658	936	325	527	750	174	282	402

Tabel cedare caldura RADIATOARE HEKO LIDO - in Watt conform EN 442									
	90/70/20°C			75/65/20°C			55/45/20°C		
LATIME	INALTIME			INALTIME			INALTIME		
[mm]		1150	1800		1150	1800		1150	1800
500		424	646		340	517		182	277

Tabel cedare caldura RADIATOARE HEKO URLA - in Watt conform EN 442									
	90/70/20°C			75/65/20°C			55/45/20°C		
LATIME	INALTIME			INALTIME			INALTIME		
[mm]	800	1200	1800	800	1200	1800	800	1200	1800
500	405	603	892	322	479	710	169	252	374
600	467	695	1029	371	553	819	195	291	432