



| Tabel cedare caldura RADIATOARE OTEL HEKO DIVA - in Watt conform EN 442 | | | | | | | | | | | | |
|---|------------|------|------|------|------------|------|------|------|------------|-----|-----|-----|
| | 90/70/20°C | | | | 75/65/20°C | | | | 55/45/20°C | | | |
| INALTIME | LATIME | | | | LATIME | | | | LATIME | | | |
| [mm] | 300 | 380 | 500 | 580 | 300 | 380 | 500 | 580 | 300 | 380 | 500 | 580 |
| 1800 | 1033 | 1292 | 1680 | 1938 | 823 | 1028 | 1337 | 1543 | 434 | 543 | 706 | 815 |

| Tabel cedare caldura RADIATOARE OTEL HEKO DIVA - in Watt conform EN 442 | | | | | | | | | | | | |
|---|------------|-----|------|------|------------|-----|-----|------|------------|-----|-----|------|
| | 90/70/20°C | | | | 75/65/20°C | | | | 55/45/20°C | | | |
| INALTIME | LATIME | | | | LATIME | | | | LATIME | | | |
| [mm] | 580 | 780 | 980 | 1180 | 580 | 780 | 980 | 1180 | 580 | 780 | 980 | 1180 |
| 600 | 683 | 911 | 1139 | 1367 | 548 | 731 | 914 | 1097 | 296 | 394 | 493 | 591 |

| Tabel cedare caldura RADIATOARE ALUMINIU HEKO DRAMA - in Watt conform EN 442 | | | | | | | | | | | | |
|--|------------|------|------|------|------------|-----|------|------|------------|-----|-----|-----|
| | 90/70/20°C | | | | 75/65/20°C | | | | 55/45/20°C | | | |
| INALTIME | LATIME | | | | LATIME | | | | LATIME | | | |
| [mm] | 280 | 375 | 475 | 565 | 280 | 375 | 475 | 565 | 280 | 375 | 475 | 565 |
| 1800 | 865 | 1154 | 1442 | 1730 | 685 | 914 | 1142 | 1370 | 357 | 476 | 595 | 714 |

| Tabel cedare caldura RADIATOARE ALUMINIU HEKO DRAMA - in Watt conform EN 442 | | | | | | | | | | | | |
|--|------------|------|------|------|------------|-----|------|------|------------|-----|------|------|
| | 90/70/20°C | | | | 75/65/20°C | | | | 55/45/20°C | | | |
| INALTIME | LATIME | | | | LATIME | | | | LATIME | | | |
| [mm] | 660 | 850 | 1040 | 1230 | 660 | 850 | 1040 | 1230 | 660 | 850 | 1040 | 1230 |
| 600 | 789 | 1014 | 1240 | 1465 | 625 | 804 | 982 | 1161 | 326 | 419 | 512 | 605 |